

13/625/757 - Lithium-ion battery

Material number 013/625/757

Page: 1 of 10

1. Product and company identification**Product identifier**

Trade name: 13/625/757 - Lithium-ion battery

Relevant identified uses of the substance or mixture and uses advised againstGeneral use: Lithium-ion battery for orthopedic procedures
For commercial user only.**Details of the supplier of the safety data sheet**Company name: Otto Bock Health Care
Street/POB-No.: 3820 W. Great Lakes Drive
Postal Code, city: Salt Lake City, UT 84120
USAWWW: www.ottobockus.com

Telephone: +1 (801) 956-2400

Telefax: +1 (801) 956-2401

Dept. responsible for information:

Quality Department,
Telephone: +1 (801) 954-2304 (7 AM – 3 PM, Mountain Time), Email:
USRegulatory@ottobock.com

Additional information: This safety data sheet pertains to the following products:

13E210 - Power Pack für DynamicArm
625B11 - Lithium-Ion Akkupack für Kniegelenk
757B35=3 - MyoEnergy Integral
757VAB1 - VASI Li-Ion Batterie**Emergency phone number****CHEMTREC, Telephone: +1 (800) 424-9300****Transport:****CONSULTANK Lutz Harder GmbH (Contract QUALI003)****Telephone: +49 (0)178-4337434 (from USA: 01149 178 4337434)****2. Hazards identification****Emergency overview**

Appearance: Form: solid

Odor: odorless

Classification: This material is classified as not hazardous.

Regulatory status

This material is not considered hazardous by the U.S. OSHA Hazard Communication Standard (29 CFR 1910.1200) and SIMDUT in Canada.

Hazards not otherwise classified

The battery is hermetically sealed.

danger of releasing ingredients, mentioned in section 3, by damaging the battery

- with strong mechanical action,
- in case of heating and/or Fire,
- with influence of water,
- short circuit.

Hazard statements:

Limited evidence of a carcinogenic effect. May cause sensitisation by skin contact.

Electrolyte, organic:

Flammable. Vapors irritate eyes, mucous membranes and respiratory system. Vapors may cause drowsiness and dizziness.

After contact with water: formation of Hydrogen fluoride (Fatal in contact with skin. Fatal if swallowed. Fatal if inhaled. Causes severe skin burns and eye damage.).

see section 11: Toxicological information

3. Composition / Information on ingredients

Chemical characterization: Lithium-ion battery - Article.

The chemical materials are stored in a hermetically sealed metal case.

Contains Aluminium (10 - 40%), Graphite (10 - 20%), Carbon (10 - 20%), Copper (5 - 15%).

Hazardous ingredients:

CAS No.	Designation	Content	Classification
CAS 12190-79-3	Cobalt lithium dioxide	20 - 40 %	Sensitization - skin - Category 1. Carcinogenicity - Category 2.
CAS -	Electrolyte, organic	5 - 20 %	Flammable Liquid - Category 3.

4. First aid measures

General information: In case of damaged battery cases: Release of dangerous ingredients possible.
In case of heating: Generates dangerous gases or fumes in contact with.

In case of inhalation: In case of damaged battery cases:
Provide fresh air. Keep victim at rest in half upright position. Seek medical attention.

Following skin contact: In case of damaged battery cases / In case of exposure to hazardous ingredients:
Clean with plenty of water. If possible, also wash with polyethylene glycol 400.
Take off immediately all contaminated clothing.

After eye contact: In case of damaged battery cases / In case of exposure to hazardous ingredients:
Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Afterwards, consult an ophthalmologist immediately.

After swallowing: Induce vomiting when the affected person is not unconscious.

In case of damaged battery cases / In case of exposure to hazardous ingredients:
Drink large quantities of water.

Do not induce vomiting. Risk of perforation in case of vomiting!
Immediately get medical attention. Do not try to neutralize.

13/625/757 - Lithium-ion battery

Material number 013/625/757

Page: 3 of 10

Most important symptoms/effects, acute and delayed

No hazardous reaction when handled and stored according to provisions.
In case of damaged battery cases / In case of exposure to hazardous ingredients:
May cause an allergic skin reaction. Irritation. May cause drowsiness or dizziness.

Information to physician

Treat symptomatically.

5. Fire fighting measures

Flash point/flash point range:

no data available

Auto-ignition temperature: no data available

Suitable extinguishing media:

Dry chemical powder, Extinguishing agent on the basis of sodium chloride, sodium hydrogen carbonate, limestone, or with metal extinguishing powder.

Extinguishing media which must not be used for safety reasons:

Water, foam.

Specific hazards arising from the chemical

In case of fire may be liberated: hydrogen fluoride, carbon monoxide and carbon dioxide.

Protective equipment and precautions for firefighters:

Wear a self-contained breathing apparatus and chemical protective clothing.

6. Accidental release measures

Personal precautions: In case of damaged battery cases:

Remove all sources of ignition.

Provide fresh air. Avoid contact with skin and eyes.

Wear suitable gloves.

In case of development of vapors or dust:

Do not inhale vapors or dust particles.

Environmental precautions:

Discharge into the environment must be avoided.

Methods for clean-up:

Take up mechanically. Dispose of waste according to applicable legislation.

Electrolyte, organic: Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents) and place in closed containers for disposal. Final cleaning.

7. Handling and storage**Handling**

Advices on safe handling: Provide adequate ventilation, and local exhaust as needed.

Avoid damaged batteries.

In case of damaged battery cases: Avoid exposure.

Precautions against fire and explosion:

Avoid short circuit. Avoid damaged batteries.

In case of damaged battery cases: Remove all sources of ignition.

Storage

Requirements for storerooms and containers:

- Provide adequate ventilation. Store in a dry place.
- Protect from: humidity, heat, UV-radiation/sunlight.
- Storage temperature: -68 °F up to 95 °F.
- Air humidity: 45% up to 85%.

Hints on joint storage: Do not store together with strong acids, strong oxidizing agents.

8. Exposure controls / personal protection

Exposure guidelines

Occupational exposure limit values:

CAS No.	Designation	Type	Limit value
12190-79-3	Cobalt lithium dioxide	USA: ACGIH: TWA	0.02 mg/m ³
		USA: NIOSH: TWA	0.05 mg/m ³
		USA: OSHA: TWA	0.1 mg/m ³
7429-90-5	Aluminium	NIOSH: Ceiling	5 mg/m ³
		USA: ACGIH: TWA	1 mg/m ³
		USA: NIOSH: TWA	10 mg/m ³
		USA: NIOSH: TWA	5 mg/m ³
		USA: OSHA: TWA	15 mg/m ³
7782-42-5	Graphite	USA: OSHA: TWA	5 mg/m ³
		USA: ACGIH: TWA	2 mg/m ³
		USA: NIOSH: TWA	2.5 mg/m ³
		USA: OSHA: TWA	15 mg/m ³
		USA: OSHA: TWA	15 mppcf
7440-44-0	Carbon	USA: OSHA: TWA	5 mg/m ³
		USA: OSHA: TWA	15 mg/m ³
		USA: OSHA: TWA	5 mg/m ³
7440-50-8	Copper	USA: ACGIH: TWA	0.2 mg/m ³
		USA: ACGIH: TWA	1 mg/m ³
		USA: NIOSH: TWA	1 mg/m ³
		USA: OSHA: TWA	0.1 mg/m ³
		USA: OSHA: TWA	1 mg/m ³

Biological limit values:

CAS No.	Designation	Type	Limit value	Parameter	Sampling
12190-79-3	Cobalt lithium dioxide	USA: ACGIH-BEI, blood	1 µg/L	Cobalt	end of shift at end of workweek
		USA: ACGIH-BEI, urine	15 µg/L	Cobalt	end of shift at end of workweek

Additional information: The chemical materials are stored in a sealed battery case.

Engineering controls

- In case of damaged battery cases: Provide adequate ventilation.
- In case of development of vapors or dust: The use of local exhaust ventilation is recommended.
- See also information in chapter 7, section storage.

Chemical stability: Stable under recommended storage conditions.

Possibility of hazardous reactions

Fire hazard in case of technical defects.

In case of damaged battery cases:

Electrolyte, organic: Flammable.

After contact with water: formation of Hydrogen fluoride.

Conditions to avoid: > 212 °F: Generation of heat. Ignition.

Protect from: humidity, water, marine water, heat, UV-radiation/sunlight

Avoid short circuit. Avoid damaged batteries.

In case of damaged battery cases:

Keep away from sources of ignition. - No smoking. Protect from: water.

Incompatible materials: Keep away from strong acids and strong oxidizing agents.

In case of damaged battery cases:

Electrolyte, organic: Keep away from water.

Hazardous decomposition products:

In case of fire may be liberated: hydrogen fluoride, carbon monoxide and carbon dioxide.

Thermal decomposition: no data available

11. Toxicological information

Toxicological tests

Toxicological effects:

Acute toxicity (oral): Lack of data.

Acute toxicity (dermal): Lack of data.

Acute toxicity (inhalative): Lack of data.

Skin corrosion/irritation: Lack of data.

Eye damage/irritation: Lack of data.

Sensitisation to the respiratory tract: Lack of data.

Skin sensitisation: Lack of data.

Germ cell mutagenicity/Genotoxicity: Lack of data.

Carcinogenicity: Lack of data.

Reproductive toxicity: Lack of data.

Effects on or via lactation: Lack of data.

Specific target organ toxicity (single exposure): Lack of data.

Specific target organ toxicity (repeated exposure): Lack of data.

Aspiration hazard: Lack of data.

Other information:

In case of damaged battery cases:

cobalt lithium dioxide:

Limited evidence of a carcinogenic effect. May cause sensitisation by skin contact.

(Cobalt: LDLo Guinea pig oral 20 mg/kg)

Electrolyte, organic:

Vapors irritate eyes, mucous membranes and respiratory system.

Vapors may cause drowsiness and dizziness.

After contact with water: formation of Hydrogen fluoride (Fatal in contact with skin. Fatal if swallowed. Fatal if inhaled. Causes severe skin burns and eye damage.).

13/625/757 - Lithium-ion battery

Material number 013/625/757

Page: 7 of 10

12. Ecological information**Ecotoxicity**

Further details: no data available

Mobility in soil

no data available

Persistence and degradability

Further details: Product is not biodegradable.

Additional ecological information


General information: Discharge into the environment must be avoided.

13. Disposal considerations**Product**

Recommendation: Dispose of waste according to applicable legislation.

Contaminated packagingRecommendation: Dispose of waste according to applicable legislation.
Packing can be recycled or disposed of.**14. Transport information****USA: Department of Transportation (DOT)**

Identification numbers: UN3090
Proper shipping name: UN 3090, Lithium metal batteries
DOT hazard class or division: 9
Label codes: 9
Packaging - Exceptions: 185
Packaging - Non-bulk: 185
Packaging - Bulk: 185
Quantity limitations - Passenger aircraft / rail: Forbidden
Quantity limitations - Cargo only: 35 kg
Vessel stowage - Location: A



13/625/757 - Lithium-ion battery

Material number 013/625/757

Page: 8 of 10

Sea transport (IMDG)

UN number: UN 3480
Proper shipping name: UN 3480, LITHIUM ION BATTERIES
IMDG: Class 9, Subrisk -
Packing Group: -
EmS: F-A, S-I
Special provisions: 188, 230, 310, 348, 376, 377
Limited quantities: 0
EQ: E0
Contaminated packaging - Instructions: P903, P908, P909, LP903, LP904
Contaminated packaging - Provisions: -
IBC - Instructions: -
IBC - Provisions: -
Tank instructions - IMO: -
Tank instructions - UN: -
Tank instructions - Provisions: -
Stowage and handling: Category A. SW19
Properties and observations: Electrical batteries containing lithium ion encased in a rigid metallic body. Lithium ion batteries may also be shipped in or packed with equipment. Electrical lithium batteries may cause fire due to an explosive rupture of the body caused by improper construction or reaction with contaminants.
Marine pollutant: no
Segregation group: none

Air transport (IATA)

UN/ID number: UN 3480
Proper shipping name: UN 3480, LITHIUM ION BATTERIES
ICAO/IATA: Class 9
Hazard: Miscellaneous
EQ: E0
Passenger Ltd.Qty.: Forbidden
Passenger: Pack.Instr. See 965 - Max. Net Qty/Pkg. See 965
Cargo: Pack.Instr. See 965 - Max. Net Qty/Pkg. See 965
Special Provisioning: A88 A99 A154 A164 A183
ERG: 9F

13/625/757 - Lithium-ion battery

Material number 013/625/757

Page: 9 of 10

15. Regulatory information**National regulations - U.S. Federal Regulations**

Cobalt lithium dioxide:	TSCA Inventory: listed TSCA HPVC: not listed
Aluminium:	TSCA Inventory: listed TSCA HPVC: not listed Other Environmental Laws: SARA Title III Section 313, Toxic Release: Conc. 1.0% / Threshold Standard NIOSH Recommendations: Occupational Health Guideline: 0022
Graphite:	TSCA Inventory: listed TSCA HPVC: not listed NIOSH Recommendations: Occupational Health Guideline: 0306
Carbon:	TSCA Inventory: listed TSCA HPVC: not listed NIOSH Recommendations: Occupational Health Guideline: 0307
Copper:	TSCA Inventory: listed TSCA HPVC: not listed Clean Water Act: Priority Pollutant: yes Other Environmental Laws: CERCLA: RQ 5000* lbs. Marine Pollutant: listed as severe pollutant. RCRA Groundwater Monitoring: Methods 6010, 7210 / PQL 60, 200 SARA Title III Section 313, Toxic Release: Conc. 1.0% / Threshold Standard NIOSH Recommendations: Occupational Health Guideline: 0150*

National regulations - U.S. State Regulations

Cobalt lithium dioxide:	California Proposition 65: cancer Rhode Island HSL: listed
-------------------------	---

National regulations - Great Britain

Hazchem-Code: 4W

16. Other information

Hazard rating systems:



NFPA Hazard Rating:

Health: 0 (Minimal)

Fire: 1 (Slight)

Reactivity: 0 (Minimal)

HMIS Version III Rating:

Health: 0 (Minimal)

Flammability: 1 (Slight)

Physical Hazard: 0 (Minimal)

Personal Protection: X = Consult your supervisor
in case of damaged battery cases: NFPA/HMIS: F2

HEALTH	0
FLAMMABILITY	1
PHYSICAL HAZARD	0
	X

Reason of change: Changes in section 14: IMDG 2015

Date of first version: 10/26/2010

Department issuing data sheet

Contact person: see section 1: Dept. responsible for information

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.