

Trias 1C30-1

Secure as expected.

Trias was designed for moderately active individuals who navigate indoor and familiar outdoor environments and place a high value on consistent stability when walking.

Designed for optimal outcomes:

- Flexible double springs provide dampening at heel strike and soft rollover
- Triangular design for balanced, controlled movements when walking on uneven surfaces
- Lightweight design
- Protected against fresh, salt and chlorine water
- Water runoff channels on connection adapter and drainage holes in footshell prevent water from collecting in the interior of the prosthesis
- Slim footshell option
- Compatible with all Ottobock microprocessor-controlled knee joints

More than a foot.
A foundation.



©2021 Otto Bock HealthCare LP · 19591 · 08/21

Technical data

K-Level	K3
Max. body weight	275 lbs / 125 kg
Side	Neutral foot module (N)
Sizes	21–30 cm
Weight without footshell*	12.1 oz / 345 g
Footshell shape	Slim shape with 20 +/- 5 mm heel height (21-26 cm) Normal shape with 10 +/- 5 mm heel height (21-30 cm)
Footshell color	beige (4), light brown (15)
Weight with normal footshell*	22 oz / 625 g
Build height with normal footshell*	4 7/16 in / 113 mm

*Reference size is 26 cm.



Trias 1C30-1



Order form

Customer		Shipping address (if different from customer address)	
Customer no.	<input type="text"/>	Customer no.	<input type="text"/>
Company	<input type="text"/>	Company	<input type="text"/>
Street	<input type="text"/>	Street	<input type="text"/>
Postal code/city	<input type="text"/>	Postal code/city	<input type="text"/>
O&P professional	<input type="text"/>	PO no.	<input type="text"/>

Quantity	Article no.	Side	Size	Stiffness	P /	Color	Shape
	1C30-1=				P /		
	1C30-1=				P /		

Order example for 1C30-1 Trias with normal footshell

1C30-1=R26-1-P/4

Order example for 1C30-1 Trias with slim footshell

1C30-1=R26-1-P/4S

Side	Size [cm]	Color	Shape
Right R	21, 22, ..., 30	Beige 4	Normal
Left L		Light brown 15	Slim S

The scope of delivery for the 1C30-1 Trias includes the 2C3-1 footshell with connection cap and a spectra sock. The footshell is available in a slim version with 20 mm heel height and a normal version with 10 mm heel height.



Stiffness chart

Body weight \ Sizes	21 cm	22 cm	23 cm	24 cm	25 cm	26 cm	27 cm	28 cm	29 cm	30 cm
	99 - 133 lbs (45 - 60 kg)	1	1	1	1	-	-	-	-	-
134 - 177 lbs (61 - 80 kg)	2	2	2	2	1	1	1	1	-	-
178 - 210 lbs (81 - 95 kg)	-	-	3	3	2	2	2	2	1	1
211 - 244 lbs (96 - 110 kg)	-	-	-	-	3	3	3	3	2	2
245 - 275 lbs (111 - 125 kg)	-	-	-	-	-	-	4	4	3	3

■ Normal and slim footshell available ■ Normal footshell available

Recommended combinations**

TT***	TF***
<p>4R140 One-way valve + 6Y95 Caleo 3D liner or 6Y92 Caleo liner + 453A30/40 ProFlex Plus sealing sleeve or 4R220 Dynamic Vacuum System pump + 6Y94 Dynamic Vacuum System liner or 6A30=20N Shuttle lock + 6Y43 Skeo Pure liner</p>	<p>6Y110 Skeo Sealing liner + 21Y21 ClickValve or 4R160 KISS Lanyard System + 6Y85 Skeo Skinguard / 6Y88 Skeo 3D</p>
<p>4R10=111 Quickchange adapter</p>	<p>3R78 3R80 3R60/-PRO 3R106/-PRO</p>
<p>6R8=* Foam cover or 6R18=* Foam cover (if no Quickchange is used)</p>	<p>4R57=WR Rotation adapter (above the knee) 4R10=111 Quickchange adapter (below knee)</p>
	<p>3S107=* (if no Quickchange is used)</p>

** All components are sold separately and are available Ottobock products that are compatible with the 1C30-1 Trias foot, which helps ensure optimal performance. Practitioners need to select components based upon individual patient criteria.

*** All shown components except the 3R78, 3R60/-PRO, 3R106/-PRO knee joints and the foam covers 6R8=*, 6R18=* and 3S107=* are waterproof.